Supplementary Table 10. THB–outcome association stratified by acquisition characteristics

Stratum	Subgroup	Number	Outcome	THB OR per SD (95% CI)
Overall	All patients	6,124	1,518	1.19 (1.11–1.27)
Scanner vendor	Philips	2,737	702	1.28 (1.16–1.41)
	Siemens	2,432	528	1.11 (1.00–1.24)
	GE	954	288	1.26 (1.04–1.54)
Field strength[a)]	3T	5,537	1,383	1.19 (1.11–1.28)
	1.5T	154	26	Insufficient events
	Unknown	426	108	1.31 (1.03–1.67)
Slice thickness	≤3 mm	4,789	1,130	1.11 (1.03–1.20)
	>3 mm	1,335	388	1.38 (1.21–1.58)
Sequence	SWI	4,291	942	1.14 (1.05–1.23)
	SWAN	955	288	1.26 (1.04–1.54)

Each row is an independent model; the THB composite was rebuilt within the subset and adjusted for the same clinical covariates. Odds ratios are per 1 SD for 3-month poor outcome. Strata with fewer than 30 events were not modelled.
THB, total hemorrhagic burden; OR, odds ratio; SD, standard deviation; SWI, susceptibility-weighted imaging; SWAN, susceptibility-weighted angiography.
[a)]Field strength was inferred from the scanner model name (approximate); "1.5/3T (Achieva)" is a model sold in both variants.